



| Diametri | Limiti | dk    | d1   | P      | TX  |
|----------|--------|-------|------|--------|-----|
| 3,0      | Min.   | 5,65  | 2,80 | ~ 1,45 | T10 |
|          | Max    | 6,05  | 3,20 |        |     |
| 3,5      | Min.   | 6,65  | 3,10 | ~ 2,15 | T15 |
|          | Max    | 7,05  | 3,40 |        |     |
| 4,0      | Min.   | 7,50  | 3,50 | ~ 2,52 | T20 |
|          | Max    | 8,00  | 3,80 |        |     |
| 4,5      | Min.   | 8,50  | 3,70 | ~ 2,80 | T25 |
|          | Max    | 9,00  | 4,00 |        |     |
| 5,0      | Min.   | 9,64  | 3,70 | ~ 3,20 | T25 |
|          | Max    | 10,00 | 4,40 |        |     |
| 6,0      | Min.   | 11,50 | 4,80 | ~ 4,70 | T30 |
|          | Max    | 12,10 | 5,20 |        |     |
| 8,0      | Min.   | 14,30 | 6,80 | ~ 5,50 | T40 |
|          | Max    | 15,00 | 7,20 |        |     |
| 10,0     | Min.   | 17,40 | 8,00 | ~ 6,60 | T40 |
|          | Max    | 18,20 | 8,50 |        |     |
| 12,0     | Min.   | 21,00 | 9,50 | ~ 6,00 | T50 |
|          | Max    | 22,00 | 9,80 |        |     |

- Acciaio temperato: C10B21
- Durezza superficiale: HV 420-500
- Durezza a cuore: HV 300-390
- Parte filettata: come da listino (Es. 4,0x30/18 = filetto 18)