


Collare Inox per tubo Acciaio (con tassello standard e vite di giunzione)



Prove di trazione e carico

M8	daN	daN
3/8	100	160
1/2	100	160
3/4	100	160
1 1/4	100	160
1 1/2	100	160
2	100	160
2 1/2	100	160
3	100	160
4	100	160
M10	daN	daN
2 1/2	160	400
3	160	400
4	160	400
5	160	400
6	160	400
8	160	400



Codice	Ø	Piatto	Att.	Pz. box	Pz. Blister	Perno	Tassello
10001/I	3/8	20x2	M8	100	2	8x90	10x60
10002/I	1/2	20x2	M8	100	2	8x90	10x60
10003/I	3/4	20x2	M8	100	2	8x90	10x60
10004/I	1	20x2	M8	100	2	8x90	10x60
10005/I	1 ¼	20x2	M8	100	2	8x90	10x60
10006/I	1 ½	20x2	M8	100	2	8x90	10x60
10007/I	2	20x2	M8	100	2	8x90	10x60
10008/I	2 ½	20x2	M8	50	2	8x90	10x60
10009/I	3	20x2	M8	50	2	8x90	10x60
10010/I	4	20x2	M8	50	2	8x90	10x60
10011/I	2 ½	29x2	M10	50	2	10x120	12x60
10012/I	3	29x2	M10	50	2	10x120	12x60
10013/I	4	29x2	M10	50	2	10x120	12x60
10013A/I	5	29x2	M10	50	2	10x120	12x60
10014/I	6	29x2	M10	50	2	10x120	12x60
10015/I	8	29x2	M10	50	2	10x120	12x60

Collare realizzato in acciaio INOX AISI 304 e dotato di viterie in INOX AISI 304.