


Collare Inox per tubo PVC (con tassello standard e vite di giunzione)



Prove di trazione e carico

	daN	daN
40	160	400
50	160	400
63	160	400
75	160	400
80	160	400
90	160	400
100	160	400
110	160	400
125	160	400
140	160	400
160	160	400
200	160	400
250	160	400
315	160	400
350	160	400
400	160	400



Codice	Ø	Piatto	Att.	Pz. box	Pz. Blister	Perno	Tassello
10301/I	40 mm	29x2	M10	50	2	10x120	12x60
10302/I	50 mm	29x2	M10	50	2	10x120	12x60
10303/I	63 mm	29x2	M10	50	2	10x120	12x60
10304/I	75 mm	29x2	M10	50	2	10x120	12x60
10305/I	80 mm	29x2	M10	50	2	10x120	12x60
10306/I	90 mm	29x2	M10	50	2	10x120	12x60
10307/I	100 mm	29x2	M10	50	2	10x120	12x60
10308/I	110 mm	29x2	M10	50	2	10x120	12x60
10309/I	125 mm	29x2	M10	50	2	10x120	12x60
10309A/I	130 mm	29x2	M10	50	2	10x120	12x60
10310/I	140 mm	29x2	M10	50	2	10x120	12x60
10311/I	160 mm	29x2	M10	50	2	10x120	12x60
10312/I	200 mm	29x2	M10	50	2	10x120	12x60
10313/I	250 mm	29x2	M10	50	2	10x120	12x60
10314/I	315 mm	29x2	M10	50	2	10x120	12x60
10315/I	350 mm	29x2	M10	50	2	10x120	12x60
10316/I	400 mm	29x2	M10	50	2	10x120	12x60

Collare realizzato in acciaio INOX AISI 304 e dotato di viterie in INOX AISI 304.