



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Anti-crushing plug in rubber 10A 2P+E 250V S11
	Article code	RS78003
	Commercial Series	ANTI-CRUSHING SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	/							
	Current	A 10	Dimensional stability	°C -25 /+70							
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750							
	Degree of protection	IP 20	Working temperature	°C , -15 + 35							
	Impact Resistance	IK 8	Weight	kg 0,024							
	Insulation Resistance	MΩ >10									
	Dimensions LxDxH	cm 8,2x3,2x1,5									
	Behaviour with chemical and atmospheric agents										
	Saline Solution	Acids		Bases		Solvents			Mineral Oil	UV rays	
	Resistant	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	Resistant	Resistant
	●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Limited Resistant ●	Limited Resistant ●	Resistant ●	Resistant ●	Resistant ●	Resistant ●

<i>Standards</i>	CEI 23-50	2011/65/UE
------------------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,024
	Package innerbox		90	2,25
	Packaging		720	18,62



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi