














Illustrative picture

**SPECIFICS**

Description	Product type	Anti-crushing plug in rubber 16A 2P+E 250V S11
	Article code	<b>RS78006</b>
	Commercial Series	ANTI-CRUSHING SERIES

General Data	Poles	N° 2P+E	Type of material	/
	Current	A 16	Dimensional stability	°C -25 /+70
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750
	Degree of protection	IP 20	Working temperature	°C , -15 + 35
	Impact Resistance	IK 8	Weight	kg 0,034
	Insulation Resistance	MΩ >10		
	Dimensions LxDxH	cm 9,3x4,3x1,8		

Behaviour with chemical and atmospheric agents										
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Limited Resistant 	Limited Resistant 	Resistant 	Resistant 	Resistant 	Resistant 

Standards	CEI 23-50	2011/65/UE
-----------	-----------	------------

Features package	Descriptions		N/pieces	Weight/kg
	Article		1	0,034
	Package innerbox		25	0,94
	Packaging		300	11,9



Rev	Date	Technical Manager
01	7/1/20	<i>Romano Rosi</i>