



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Extra flat adaptor; Pl: 16A 2P+E 250V S17; Sock: IT Biv 10/16A 2P+E 250V (3x)
	Article code	RS78132
	Commercial Series	EMILIA SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	Halogen free
	Current	A 16	Dimensional stability	°C -25 /+70
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750
	Degree of protection	IP 20	Working temperature	°C , -15 + 35
	Impact Resistance	IK 8	Weight	kg 0,072
	Insulation Resistance	MΩ >10		
	Dimensions LxDxH	cm 8x6,2x4,3		

Behaviour with chemical and atmospheric agents											
Saline Solution	Acids		Bases		Solvents				Mineral Oil	UV rays	
	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol			
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant	

<i>Standards</i>	CEI 23-50	CEI 23-57	2011/65/UE
------------------	-----------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,072
	Package innerbox		20	1,54
	Packaging		160	12,52



Reg. A.E.E.n° IT7100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Extra flat adaptor; Pl: 16A 2P+E 250V S17; Sock: IT Biv 10/16A 2P+E 250V (3x)
	Article code	RS78133
	Commercial Series	EMILIA SERIES

<i>General Data</i>	Poles	N° 2P+E	Type of material	Halogen free						
	Current	A 16	Dimensional stability	°C -25 /+70						
	Voltage	V~ 250	Resistance glow wire test	°C +650 / +750						
	Degree of protection	IP 20	Working temperature	°C , -15 + 35						
	Impact Resistance	IK 8	Weight	kg 0,072						
	Insulation Resistance	MΩ >10								
	Dimensions LxDxH	cm 8x6,2x4,3								
	Behaviour with chemical and atmospheric agents									
	Acids		Bases		Solvents				Mineral Oil	UV rays
Saline Solution	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol		
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI 23-50	CEI 23-57	2011/65/UE
------------------	-----------	-----------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,072
	Package innerbox		20	1,54
	Packaging		160	12,52



CERTIFICATON° 9105.ROSI - UNI EN ISO 9001:2015



Reg. A.E.E n° IT7100000010057



Rev	Date	Technical Manager
01	7/1/20	Romano Rosi