



Illustrative picture

SPECIFICS

<i>Description</i>	Product type	Adaptor
	Article code	1823
	Commercial Series	Powershell

<i>General Data</i>	Poles	N° 2P+E	Type of material	Thermoplastic					
	Current	A 16	Type of terminal	Screw PH2					
	Voltage	V~ 200-250	Terminal inlet diameter	mm 3,7					
	Earth contact position	h T+TL	Cable clamp tightening capacity	mm 6,5 - 15					
	Degree of protection	IP 67	Dimensional stability	°C -25 /+70					
	Impact Resistance	IK 8	Resistance glow wire test	°C +650 / +850					
	Insulation Resistance	MΩ >10	Working temperature	°C , -25 + 55					
	Dimensions LxDxH	cm 7X7X23	Weight	kg 0,1447					
	Behaviour with chemical and atmospheric agents								
		Acids		Bases		Solvents			Mineral Oil
Saline Solution	Concentrated	Diluted	Concentrated	Diluted	Hexane	Benzol	Acetone	Alcohol	
Resistant	Limited Resistant	Resistant	Resistant	Resistant	Limited Resistant	Limited Resistant	Resistant	Resistant	Resistant

<i>Standards</i>	CEI EN 60309-1	CEI EN 60309-2	2014/35/UE
------------------	----------------	----------------	------------

<i>Features package</i>	<i>Descriptions</i>		<i>N/pieces</i>	<i>Weight/kg</i>
	Article		1	0,1447
	Package innerbox		10	1,537
	Packaging			



CERTIFICATO N° 9105.ROS3 - UNI EN ISO 9001:2015



Reg. A.E.E n° IT17100000010057

Rev	Date	Technical Manager
01	7/1/20	Romano Rosi